



52744 Park Six Court • Elkhart • IN • 46514  
Phone • (574) 970-0198 Fax • (574) 970-0285



### Features

- Magnetic sensor activated pump, one direction only.
- Controller with on light, variable flow, on/off power switch, and on/off pump switch
- Patented variable flow control switch
- Built in smart chip 12 volt charger, included with every unit
- Manual pressure regulator for variable pad pressure
- Applicator pad is constructed of 4" wide natural lambs skin, with 1.5" thick pile
- Aluminum drip and rinse tray, included with every unit
- Base easily carries various sizes of chemical containers

### Technical Specifications

Model #	HMMIII-28	HMMIII-36	HMMIII-48
Part #	F-HUMMVIII-28	F-HUMMVIII-36	F-HUMMVIII-48
Head Size	28 inch	36 inch	48 inch
Application Rate	15,000 ft <sup>2</sup> /hr	20,000 ft <sup>2</sup> /hr	27,500 ft <sup>2</sup> /hr
Pump/Motor	12 VDC 2.2 gpm open 70 psi max	12 VDC 2.2 gpm open 70 psi max	12 VDC 2.2 gpm open 70 psi max
Battery	12 volt, 7AH	12 volt, 7AH	12 volt, 7AH
Battery Charger	Automatic, 120V/60Hz .4amp/14.7 VDC	Automatic, 120V/60Hz .4amp/14.7 VDC	Automatic, 120V/60Hz .4amp/14.7 VDC
Frame	All Steel Epoxy Coated	All Steel Epoxy Coated	All Steel Epoxy Coated
Wheels (Non-Marking)	2 - 8" Ball Bearing Fixed 2 - 3" Swivel	2 - 8" Ball Bearing Fixed 2 - 3" Swivel	2 - 8" Ball Bearing Fixed 2 - 3" Swivel
Handle Height	Variable, 32"- 40"	Variable, 32"- 40"	Variable, 32"- 40"
Dimension	21.2" X 21" X 33.5	21.2" X 21" X 33.5	21.2" X 21" X 33.5